

Sila Grow Bunker Cover

- Excellent UV resistance
- Protect fodder by eliminating exposure to light, water and air
- Superior mechanical properties and strong resistance to impact and tearing
- Thickness: 100um to 200um
- Width: up to 60m (200ft)
- Color: white/black

Size&Packaging:

- loose pack in skid

Note: The size of products can be customized by customer needs.



Typical Properties Of Sila Grow Bunker cover

PROPERTY		UNITS	+ / -	DATA			TEST METHOD
THICKNESS		um	5	125	150	200	
TENSILE STRENGTH	MD	Mpa	3	22	22	22	ASTMD 882
	TD			21	20	20	ASTMD 882
ENLONGATION AT BREAK	MD	%	5	500	520	520	ASTMD 882
	TD			600	620	620	ASTMD 882
ELMENDORF TEAR	MD	gm	50	330	380	410	ASTMD 1922
	TD			520	550	560	ASTMD 1922
DART IMPACT		N/um	10	380	370	370	EXXONMOBIL METHOD
DART IMPACT		gm	50	270	320	370	ASTMD 1709
WVTR		g/m ² .d.0.1Mpa	1	4	4	4	ASTMF 3722
OTR		ml/m ² .d.0.1Mpa	150	1900	1800	1650	ASTMD 3985
U.V PROTECT: GUARENTEE 12 MONTHS							

Typical Range Of Sila Grow Bunker cover

WIDTH	LENGTH	THICKNESS	CORE ID	COLOR	PACKAGING
20'-60'	100'-1000'	5mil,6mil,8mil	3" PLASTIC 3" PAPER	WHITE/BLACK	CARTON PACK IN SKID
6m-18m	30m-300m	125um,150um,200um			LOOSE PACK IN SKID
NOTE: THE SIZE OF PRODUCTS CAN BE CUSTOMIZED BY CUSTOMER NEEDS.					

Sila Grow Sales (BC) Ltd.

PH: 1-800-663-6022 or 250-804-4769 Email: office@silagrow.com Website: www.silagrow.com
Physical Add: 5121 46th Avenue SE, Salmon Arm, BC Mailing Add: PO Box 303, Salmon Arm, BC V1E 4N5