

### Sila Grow Mulch Film

- 3 layer co-extruded quality film
- UV stabilized 15 month
- Superior stretch
- Opaque to keep weeds off
- Elastic to keep film clean

**Size&Packaging:**

- 1mil4'(or5')4000' 20R/Skid
- 1mil4'(or5')6000' 16R/Skid



### Typical Properties Of Sila Grow Mulch Film

PROPERTY	UNITS	+ / -	DATA		TEST METHOD	
THICKNESS	mil	0.06	1	1.4		
TENSILE	MD	Mpa	3	39	37	ASTM D 882
STRENGTH	TD			32	30	
ENLONGATION	MD	%	5	470	510	ASTM D 882
AT BREAK	TD			515	530	
ELMENDORF	MD	gm	5	528	700	ASTM D 1922
TEAR	TD			819	990	
DART IMPACT	gm	5	230	330	ASTM D 1709	
PUNCTURE RESITANCE	N/um	10	475	450	EXXONMOBIL METHOD	
U.V PROTECT:	GUARENTEE 15 MONTH					

### Typical Range Of Sila Grow Mulch Film

WIDTH(ft)	LENGTH ( ft )	THICKNESS (mil)	CORE ID	COLOR	PACKAGING
3 - 16	4000-8000	0.8 - 2	3" PLASTIC	BLACK, CLEAR	SKID
				SILVER ON BLACK	

**Sila Grow Sales (BC) Ltd.**