

Sila Grow Bale Wrap

- 3 layer co-extruded quality film
- UV stabilized
- Strong adhesive
- Affordable quality products

Size&Packaging:

- 25um750mm1500m 40R/Skid
- 25um500mm1800m 48R/Skid



Typical Properties Of Sila Grow Bale Wrap

PROPERTY		UNITS	+ / -	DATA		TEST METHOD
THICKNESS		um	1.5	25	30	
TENSILE STRENGTH	MD	Mpa	3	41	40	ASTM D 882
	TD			31	30	
ENLARGEMENT AT BREAK	MD	%	5	470	510	ASTM D 882
	TD			515	530	
ELMENDORF TEAR	MD	gm	5	528	580	ASTM D 1922
	TD			819	880	
DART IMPACT		gm	5	215	257	ASTM D 1709
PUNCTURE RESISTANCE		N/um	10	475	470	EXXONMOBIL METHOD
STICKINESS		N/10cm ²	0.5	7.57	7.45	BEN-516
PRESTRETCH		%	10	180	180	
U.V PROTECT: GUARENTEE 12 MONTHS						

Typical Range Of Sila Grow Bale Wrap

WIDTH (mm)	LENGTH (m)	THICKNESS(u)	CORE ID	COLOR	PACKAGING
250, 500, 750	1500 1800	25, 30	3" PLASTIC 3" PAPER	WHITE, BLACK, GREEN	CARTON PACK IN SKID
NOTE: THE SIZE OF PRODUCTS CAN BE CUSTOMIZED BY CUSTOMER NEEDS.					

Sila Grow Sales (BC) Ltd.

PH: 1-800-663-6022 or 250-804-4769 Email: office@silagrow.com Website: www.silagrow.com
Physical Add: 5121 46th Avenue SE, Salmon Arm, BC Mailing Add: PO Box 303, Salmon Arm, BC V1E 4N5